



Central Portal for
Philippine Government
Procurement Opportunities

Bid Notice Abstract

Request for Quotation (RFQ)

Reference Number 9882459
Procuring Entity BATAAN PENINSULA STATE UNIVERSITY
Title BPSU MCO OPA Supply & Delivery of IT Equipment, Accessories and peripherals for the upcoming University President's Investiture
Area of Delivery Bataan

Solicitation Number:	MCO2023-06-559	Status	Pending
Trade Agreement:	Implementing Rules and Regulations		
Procurement Mode:	Negotiated Procurement - Small Value Procurement (Sec. 53.9)	Associated Components	2
Classification:	Goods	Bid Supplements	0
Category:	Information Technology Parts & Accessories & Perip		
Approved Budget for the Contract:	PHP 345,900.00	Document Request List	0
Delivery Period:	15 Day/s		
Client Agency:		Date Published	25/06/2023
Contact Person:	Riezle Clarin Muñoz Procurement Unit Capitol Site Balanga City Bataan Philippines 2100 63-47-2371341 63-932-8662730 rcmunoz@bpsu.edu.ph	Last Updated / Time	24/06/2023 10:38 AM
		Closing Date / Time	30/06/2023 17:00 PM

Description

Qty. Unit of Measure Description/Offer
 3 unit TRIPOD
 Load Capacity 4kg
 Max Height 1550mm/61.02 inches
 Retracted/Folded Height: 515mm/20.28 inches
 Leg Sections: 4
 Product Highlights
 Number of leg sections - 4
 Lightweight and easy to carry
 Load capacity: 4KG
 Material: Alluminum Alloy
 Most compatible with DSLR's
 1 unit LAPEL
 ACOUSTIC & ELECTRICAL
 Acoustic Principle - Pre-polarised pressure transducer
 Polar Pattern - Omnidirectional
 Frequency Range - 50Hz - 20kHz
 Maximum SPL - 100 dB SPL (1kHz @ 1m) dBu
 Maximum Input Level (3.5mm) -20dBV
 Microphone Preamp Gain - 20dB

Equivalent Noise Level (A-Weighted) - 22dBA
 Power Requirements - In-built rechargeable lithiumion battery charged via USB 5V, 0.3A
 Operating Time - Up to 7 hours
 Analog Inputs - 3.5mm TRS (lavalier microphone input)
 Analog Outputs - 3.5mm TRS
 Transmission Range - 200m (line of sight)
 Computer Connectivity - USB Type-C
 OS Requirements
 - macOS 10.11 above
 - Windows 10 and above
 MECHANICAL
 Weight (g)
 - TX: 30g RX: 32g
 Dimensions (mm)
 - TX Length: 44 Width: 45.3 Height: 18.3
 - RX Length: 44 Width: 45.5 Height: 18.3
 1 unit GIMBAL
 Camera Tray Dimensions
 "Maximum depth from the center of gravity on the camera
 base plate: 98 mm
 Maximum height measured from top of the camera base plate: 150 mm
 Maximum width: 205 mm"
 Accessory Port
 Mechanical: 1/4"-20, 3/8"-16 Mounting Hole, M4 Mounting Hole
 Electrical: 12V/2A Power Accessory Port, Camera Control Port, 8-pin Port
 Input Power
 "Model: RB1-2400mAh-14.4V
 Type: 18650 LiPo
 Capacity: 2400 mAh
 Energy: 34.56 Wh"
 Connections
 "Bluetooth 4.0
 USB-C"
 Working Performance
 Load Weight (Reference Value) : 3.6 kg (Handheld)
 Angular Vibration Range: $\pm 0.02^\circ$
 Maximum Controlled Rotation Speed
 Pan axis: $360^\circ/\text{s}$; Tilt Aix: $360^\circ/\text{s}$
 Roll axis: $360^\circ/\text{s}$; continuous rotation
 Mechanical Endpoint Range
 Tilt axis: $+ 205^\circ$ to $- 115^\circ$
 Roll axis: $+ 230^\circ$ to $- 90^\circ$
 Controlled Rotation Range
 Pan axis: 360° continuous rotation (Roll 360 mode)
 Tilt axis: $+180^\circ$ to -90° (Upright Mode), $+90^\circ$ to -135° (Underslung and Flashlight Mode)
 Roll axis: $\pm 30^\circ$, 360° continuous rotation
 Mechanical & Electrical Characteristics
 Working Current - Static current: ≈ 0.16 A
 Working Frequency - 2.400 GHz to 2.4835 GHz
 Transmission Power - 0 dBm
 Operating Temperature - -4° to 113° F (-20°C to 45°C)
 Weight: Approx. 3.2 lb(gimbal only), Approx. 4.0 lb (gimbal and grip included)
 "Gimbal Dimensions: Approx. $202 \times 185 \times 486$ mm"
 1 unit LAPTOP (VIDEO EDITING)
 Intel® Core™ i9 Processor
 Windows 11
 NVIDIA® GeForce RTX™ 3060 Laptop GPU 6GB GDDR6
 64GB DDR4-3200 RAM
 1TB SSD Storage
 1 year/ subscription STREAMLABS
 Live stream application
 1 year/ subscription MOTION ARRAY
 All-in-one platform for content creators, providing unlimited downloads of professional video assets, including: video templates, presets, music, sound effects, footage, stock photos, motion graphics, and plugins. It also offers video collaboration tools, an Adobe extension and a portfolio builder, all in one subscription.
 4 pcs External Video Capture Card
 High Definition Input,Output max resolution $1920 \times 1080 @ 60\text{Hz}$. Record videos directly to the hard disk without time delay. HDMI Video Capture is suitable for devices with HDMI output, such as PS4 and Switch etc. USB capture card supports 1080P 60fps High Quality Recording and live steaming also.
 male usb to female hdmi
 Compatible with Windows, Android and MacOS. And USB 2.0 high-speed transmission port
 3 pcs HDMI TO HDMI CABLE MALE TO MALE Fiber optics
 100 Meters
 2 pcs USB HUB
 7 IN 1 for USB 2.0

5 pcs HDMI (FEMALE) TO MICRO HDMI (MALE) Adapter
 for dslr
 3 pcs Micro USB (male) to USB Male
 1meter
 1 unit WIRELESS TRANSMITTER AND RECEIVER
 SDI/HDMI WIRELESS VIDEO TRANSMISSION
 "INTERFACES HDMI Input (Type A Female)
 SDI Input
 Px Antenna Interfaces (RP. SMA Male) DC input
 USB Type-C"
 "SUPPLY INTERFACES DC Power Input:6-16V
 USB Type-C Power Supply: 5V/2A
 Battery Power Supply: 6-16V DC"
 POWER CONSUMPTION <11W
 WEIGHT 206g
 "DIMENSION (L*W*H): 110*72*33.5mm
 (The Battery Plate Excluded)"
 "INPUT/OUTPUT VIDEO FORMAT HDMI:
 480p60 576p50 720p50/59.94/60 1080i50/59.94/60
 1080p23.98/24/25/29.9/30"
 FREQUENCY 5GHz
 MODULATION MODE OFDM
 TRANSMISSION POWER Maximum 21dBm
 RECEIVER SENSITIVE /
 TRANSMISSION LATENCY 0.1s
 BANDWIDTH 20MHz
 3 pcs Multifunction MEMORY CARD READER
 Micro USB OTG to USB 2.0 Adapter
 Micro USB and USB 2.0 connector
 Card slot: SD/MMC slot and SD/TF slot
 6 pcs MICRO SD
 64 Gig
 5 pcs CAMERA BATTERY
 For NIKKON Z50
 1 Audio Converter Analog to Digital
 ***** Nothing Follows *****

Created by Riezle Clarin Muñoz

Date Created 24/06/2023

The PhilGEPS team is not responsible for any typographical errors or misinformation presented in the system. PhilGEPS only displays information provided for by its clients, and any queries regarding the postings should be directed to the contact person/s of the concerned party.

© 2004,2004,2004-2023 DBM Procurement Service. All rights reserved.,DBM Procurement Service. All rights reserved.,DBM Procurement Service. All rights reserved.

[Help](#) | [Contact Us](#) | [Sitemap](#)

REQUEST FOR QUOTATION/PROPOSAL

**BPSU MCO OPA Supply &
Delivery of IT
Equipment, Accessories and
peripherals for the
upcoming University
President's Investiture**

Bidder: _____ Address: _____ E-Mail Address: _____ Contact No. _____	Office/Section _____ PR no. _____ Quotation No. _____ TIN.no. (Indicate VAT or Non-Vat) _____
---	--

MCO 2023-06-559
Philgeps-2023-06-109mco

Please quote your lowest price on the item/s listed below, subject to the General Conditions on the last page, stating the shortest time of delivery and submit your quotation duly signed by your representative not later than in the return envelope attached herewith.


RIEZEL CLARIN MUNOZ
 Procurement Unit

- Note:**
1. ALL ENTRIES MUST BE COMPLETELY FILLED-OUT & INDICATE THE NAME OF THE BRAND BEING OFFERED.
 2. DELIVERY PERIOD WITHIN SEVEN OR FIFTEEN CALENDAR DAYS (MAXIMUM)
 3. WARRANTY SHALL BE FOR A PERIOD OF THREE (3) MONTHS FOR NON-EXPENDABLE SUPPLIES, ONE (1) YEAR FOR NON-EXPENDABLE SUPPLIES FROM DATE OF ACCEPTANCE BY THE PROCURING ENTITY.
 4. PRICE VALIDITY SHALL BE FOR A PERIOD OF THIRTY (30) CALENDAR DAYS
 5. PhilGEPS REGISTRATION CERTIFICATE SHALL BE ATTACHED UPON SUBMISSION OF THE QUOTATION
 6. BIDDERS SHALL SUBMIT ORIGINAL BROCHURES SHOWING CERTIFICATE OF THE PRODUCT BEING OFFERED.

ABC P345,900.00

No.	Qty.	Unit of Measure	Description/Offer	Unit Price	Total Cost
1	3	unit	TRIPOD		
			Load Capacity 4kg		
			Max Height 1550mm/61.02 inches		
			Retracted/Folded Height: 515mm/20.28 inches		
			Leg Sections: 4		
			Product Highlights		
			Number of leg sections - 4		
			Lightweight and easy to carry		
			Load capacity: 4KG		
			Material: Alluminum Alloy		
			Most compatible with DSLR' s		
2	1	unit	LAPEL		
			ACOUSTIC & ELECTRICAL		
			Acoustic Principle - Pre-polarised pressure transducer		
			Polar Pattern - Omnidirectional		
			Frequency Range - 50Hz - 20kHz		
			Maximum SPL - 100 dB SPL (1kHz @ 1m) dBu		
			Maximum Input Level (3.5mm) -20dBV		
			Microphone Preamp Gain - 20dB		
			Equivalent Noise Level (A-Weighted) - 22dBA		
			Power Requirements - In-built rechargeable lithiumion battery charged via USB 5V, 0.3A		
			Operating Time - Up to 7 hours		
			Analog Inputs - 3.5mm TRS (lavalier microphone input)		

			<div>Analog Outputs - 3.5mm TRS</div> <div>Transmission Range - 200m (line of sight)</div> <div>Computer Connectivity - USB Type-C</div> <div>OS Requirements</div> <div>- macOS 10.11 above</div> <div>- Windows 10 and above</div> <div>MECHANICAL</div> <div>Weight (g)</div> <div>- TX: 30g RX: 32g</div> <div>Dimensions (mm)</div> <div>- TX Length: 44 Width: 45.3 Height: 18.3</div> <div>- RX Length: 44 Width: 45.5 Height: 18.3</div>		
3	1	unit	<div>GIMBAL</div> <div>Camera Tray Dimensions</div> <div>Maximum depth from the center of gravity on the camera base plate: 98 mm</div> <div>Maximum height measured from top of the camera base plate: 150 mm</div> <div>Maximum width: 205 mm</div> <div>Accessory Port</div> <div>Mechanical: 1/4" -20, 3/8" -16 Mounting Hole, M4 Mounting Hole</div> <div>Electrical: 12V/2A Power Accessory Port, Camera Control Port, 8-pin Port</div> <div>Input Power</div> <div>Model: KSI-Z400mAh-14.4V</div> <div>Type: 18650 LiPo</div> <div>Capacity: 2400 mAh</div> <div>Connections</div> <div>Bluetooth 4.0</div> <div>USB-C</div> <div>Working Performance</div> <div>Load Weight (Reference Value) : 3.6 kg (Handheld)</div> <div>Angular Vibration Range: $\pm 0.02^{\circ}$</div> <div>Maximum Controlled Rotation Speed</div> <div>Pan axis: 360°/s ; Tilt Aix: 360/s</div> <div>Roll axis: 360°/s ; continuous rotation</div> <div>Mechanical Endpoint Range</div> <div>Tilt axis: + 205° to - 115°</div> <div>Roll axis: + 230° to - 90°</div> <div>Controlled Rotation Range</div> <div>Pan axis: 360° continuous rotation (Roll 360 mode)</div> <div>Tilt axis: +180° to -90° (Upright Mode), +90° to -135° (Underslung and Flashlight Mode)</div> <div>Roll axis: $\pm 30^{\circ}$, 360° continuous rotation</div> <div>Mechanical & Electrical Characteristics</div> <div>Working Current - Static current: ≈ 0.16 A</div> <div>Working Frequency - 2.400 GHz to 2.4835 GHz</div> <div>Transmission Power - 0 dBm</div>		

			Operating Temperature - -4° to 113° F (-20°C to 45°C)		
			Weight: Approx. 3.2 lb(gimbal only), Approx. 4.0 lb (gimbal and grip included)		
			Gimbal Dimensions: Approx. 202×185×486 mm		
4	1	unit	LAPTOP (VIDEO EDITING)		
			Intel® Core™ i9 Processor		
			Windows 11		
			NVIDIA® GeForce RTX™ 3060 Laptop GPU 6GB GDDR6		
			64GB DDR4-3200 RAM		
			1TB SSD Storage		
5	1	year/ subscription	STREAMLABS		
			Live stream application		
6	1	year/ subscription	MOTION ARRAY		
			All-in-one platform for content creators, providing unlimited downloads of professional video assets, including: video templates, presets, music, sound effects, footage, stock photos, motion graphics, and plugins. It also offers video collaboration tools, an Adobe extension and a portfolio builder, all in one subscription.		
7	4	pcs	External Video Capture Card		
			High Definition Input,Output max resolution 1920×1080@60Hz. Record videos directly to the hard disk without time delay. HDMI Video Capture is suitable for devices with HDMI output, such as PS4 and Switch etc. USB capture card supports 1080P 60fps High Quality Recording and live steaming also.		
			male usb to female hdmi		
			Compatible with Windows, Android and MacOS. And USB 2.0 high-speed transmission port		
8	3	pcs	HDMI TO HDMI CABLE MALE TO MALE Fiber optics		
			100 Meters		
9	2	pcs	USB HUB		
			7 IN 1 for USB 2.0		
10	5	pcs	HDMI (FEMALE) TO MICRO HDMI (MALE) Adapter		
			for dslr		
11	3	pcs	Micro USB (male) to USB Male		
			1meter		
			WIRELESS TRANSMITTER AND RECEIVER		
			SDI/HDMI WIRELESS VIDEO TRANSMISSION		
			INTERFACES HDMI Input (Type A Female) SDI Input Px Antenna Interfaces (RP. SMA Male) DC input USB Type-C		
			SUPPLY INTERFACES DC Power Input:6-16V USB Type-C Power Supply: 5V/2A Battery Power Supply: 6-16V DC		
			POWER CONSUMPTION <11W		
			WEIGHT 206g		

12	1	unit	DIMENSION (L*W*H): 110*72*33.5mm (The Battery Plate Excluded) INPUT/OUTPUT VIDEO FORMAT HDMI: 480p60 576p50 720p50/59.94/60 1080i50/59.94/60 1080p23.98/24/25/29.9/30 FREQUENCY 5GHz MODULATION MODE OFDM TRANSMISSION POWER Maximum 21dBm RECEIVER SENSITIVE / TRANSMISSION LATENCY 0.1s BANDWIDTH 20MHz		
13	3	pcs	Multifunction MEMORY CARD READER Micro USB OTG to USB 2.0 Adapter Micro USB and USB 2.0 connector Card slot: SD/MMC slot and SD/TF slot		
14	6	pcs	MICRO SD 64 Gig		
15	5	pcs	CAMERA BATTERY For NIKKON Z50		
16	1		Audio Converter Analog to Digital		
17			***** Nothing Follows *****		

jhozle3rd6thz

Delivery Period
 Warranty
 Price Validity

Printed Name/Signature

Tel.No./Cellphone No./e-mail address

Date